


LED Ring Pendant Light

Modern rings with different lighting directions




Overview

Construction Material	Aluminium
Body Finish	Jet Black (RAL9005) Signal White (RAL9003) White Aluminium (RAL9006)
Diffuser Type	Flexible silicone
IP Rating	IP20
Mounting	Pendant with/without mounting box
Warranty	5 years



Downwards Ring	Medium Size	Large Size
ID	765mm	1465mm
OD	835mm	1535mm
CR	250mm	350mm
MW	1500mm	2500mm



Inwards/ Outwards Ring	One Size
ID	1488mm
OD	1558mm
CR	350mm
MW	2500mm

Luminaire Output

Colour Temperature	3000K 4000K
CRI	>90 Ra
Lighting Direction	Downwards Inwards Outwards
Beam Angle	120°
Operating Hours	50,000
Flicker Free	Yes
LEDs	Bridgelux 2835
Macadam Ellipse	Equal or less than 3 sdcm

Supply & Power

Voltage Range	100-277 VAC 50/60Hz
Power Factor	>0.5
Inrush Current	DC24V
Protection Class IEC	Class II
Ambient Temperature	-20°C to +40°C
Driver	Built-in



LED Ring Pendant Light

Modern rings with different lighting directions

Luminaire Variants Data

Customisations may be available, please get in touch

Variant	Type	Outer Diameter	Wattage	Lumens at 4000K	Weight
LLCUD0850W	Ring with Downwards lighting direction - Medium Size	835mm	50W	5181	3.3 kg
LLCUD1590W	Ring with Downwards lighting direction - Large Size	1535mm	90W	2848	5.9 kg
LLCUI1588W	Ring with Inwards lighting direction - One Size	1558mm	88W	4274	3.3 kg
LLCUO1599W	Ring with Outwards lighting direction - One Size	1558mm	99W	5893	3.3 kg

Options

Kelvin	3K	3000K	4K	4000K		
Finish	BK	Black Body	WT	White Body	SV	Silver Body
Installation	SM	Surface Mounted	HM	Hanging Mounted		

Added Features

Dimming	DD	DALI Dimming	DH	Mains Dimming	CC	Casambi Controlled
---------	-----------	--------------	-----------	---------------	-----------	--------------------

Code Example

LLCUI1588W4KWT Curva Ring with light directing inwards, 88W, daylight white 4000K, white body and standard non dim driver.

