



LED Linear Light with Dark Louvre Optics

Customisable linear lighting system



Overview

Construction Material	Aluminium
Body Finish	Jet Black (RAL9005) Traffic White (RAL9016)
Optics	Dark (black) louvre
Linkable	Yes
IP Rating	IP40
IK Rating	IK08
Mounting	Ceiling mounted, Suspended
Warranty	5 years



L	H	W
532mm	100mm	50mm
1064mm	100mm	50mm
1596mm	100mm	50mm
2128mm	100mm	50mm






Luminaire Output

Colour Temperature	3000K 4000K
CRI	>90 Ra
Lighting Direction	Downwards (Optional Indirect)
Beam Angle	70°
Operating Hours	50,000
Flicker Free	Yes
LEDs	Single Bin Samsung
Macadam Ellipse	Equal or less than 3 sdcm
UGR	<17

Supply & Power

Voltage Range	AC220-240V
Power Factor	>0.95
Inrush Current	60A
Protection Class IEC	Class I
Ambient Temperature	-20°C to +40°C
Driver	Integral



LED Linear Light with Dark Louvre Optics

Customisable linear lighting system

Luminaire Variants Data

Customisations may be available, please get in touch

Variant	Length	Wattage	Lumens at 4000K	Weight	Connector	Shape	Weight
LLPRDL0514W	532mm	14W	993	2.1 kg	LLPRDLLC	L connector	0.4 kg
LLPRDL1128W	1064mm	28W	2106	2.6 kg	LLPRDLTC	T connector	0.6 kg
LLPRDL1642W	1596mm	42W	3030	3.2 kg	LLPRDLXC	X connector	0.68 kg
LLPRDL2156W	2128mm	56W	3956	4.1 kg			

Options

Kelvin	3K	3000K	4K	4000K
Finish	BK	Black Body (RAL 9005)	WT	White Body (RAL9016)
Installation	SM	Surface Mounted	HM	Hanging Mounted

Mounting



Code Example


LLPRDL2156W4KBKHM

ProLine linear light with dark louvre optics 2.1m (2128mm) 56W 4000K white body, hanging mounted, no dimming or emergency

LED Linear Light with Dark Louvre Optics

Customisable linear lighting system

Luminaire Integrations




Profile Length	Indirect Lumens at 4000K
532mm	992
1064mm	1974
1596mm	2918
2128mm	3972

/UP
Indirect Light



Lumens: 1206
Beam Angle: 24°
CRI: >90Ra
IP Rating: IP20
Rotation: 350°



/SPT
Integrated Spotlight

Added Features

Added Features

Dimming/Controls	DD	DALI Dimming	DH	Mains Dimming	CC	CASAMBI Controls
Emergency	E	3H Integral Emergency				

Code Example

LLPRDL1642W3KBKSM/DH

Proline linear light with dark louvre optics 1.6m (1596mm) 42W 4000K black body, Ssurface mounted with mains dimmable driver

